ELITE Ground Support Services
Tel. No. 0800 622 6838 www.elite-gss.com

Product Guide

EUROTRAK HD HEAVY DUTY ACCESS MATS

Designed as a short and long term access solution, whilst providing effective Ground Protection and reducing damages on site.

Our EuroTrak HD Access mats have a highly engineered, non-slip traction surface, which helps reduce slippage even in the most challenging weather and ground conditions.

max **60 tonnes**

44/22Kg

A variety of Steel Fabricated Stillages are available

Specifications

Size:	2.4m [L] x 1.2m [W] x 15mm [D] Half size: 2.4m [L] x 0.6m [W] x 15mm [D]
Weight:	44Kg / 22Kg
Load:	Suggested 60 tonnes, weight tested up to 120 tonnes (depending on ground conditions and when used with a sub-base)
Material:	100% Recycled High Density Polyethylene (HDPE) and 100% recyclable
Colour:	Black

Key Features

- ✓ Vehicular/Pedestrian traction surface
- ✓ Quick and easy installation
- ✓ 6 strategically positioned hand/connection holes
- ✓ Low transportation and handling costs
- ✓ Avoids health and safety issues
- ✓ Avoids property, heritage and environmental damage
- ✓ Avoids bogged down vehicles, saving valuable time and money

Budget Options

Perhaps you don't have the budget to purchase outright, we always have a variety of solutions for you.

- **Used/second hand**
- **Buyback**
- **Lease or Finance**

Top Tip

Our EuroTrak HD Access Mats can be customised with a company name, telephone number and website (minimum order quantity required).

As an alternative option, please take a look at our DuraMatt Medium Duty Access Mats, Safe Site Matting or Steel Road Plates.

Contact Us

elite-gss.com

sales@elite-gss.com

Civil Engineering /Infrastructure

Construction Sites

Festival and Outdoor Events

Access Routes and Temporary Car Parks

How are the EuroTrak HD Access Mats connected?
The hand hole connectors slip through each hand hole enabling the mats to connect at the top with bolts and washers.

EuroTrak Hand Hole Connectors, Bolts and Washers

Installation timings
Connectors are tightened using standard bolts and oversized washers. A spanner, wrench or battery operated drill is recommended, do not over-tighten.

2 people required. 6 strategically positioned hand holes to aid manual handling

Single line connection in 2 mins

Grid connection in less than 5 mins

230m² area in approx. 2 hours (depending on ground conditions and site layout)

When driving on the mats, do not exceed 5mph

Eco-friendly and long lasting
Made from 100% Recycled High Density Polyethylene (HDPE) which is also 100% recyclable.

Additional information

Technical and Installation Guide

Elite Products Brochure

We advise not to use Steel Tracked vehicles with any composite mats unless pre-authorised and agreed beforehand. Traversing and aggressive movement on the mats may cause damage to them and the connectors, and this will be the sole responsibility of the customer and user of the mats.

Need to Natter?

0800 622 6838

elite-gss.com

News, insights and events

Product reviews and offers, answered questions and discussion tips

Shared business and industry information

'How to' use our products, installations and vlogs

ELITE Ground Support Services