




## HOARDING PANEL

A portable and temporary Hoarding Panel solution used to form a private and safe perimeter fence during demolition and construction works.

The steel Hoarding Panel is easy to install and make a solid fencing perimeter to increase your site security and privacy.

The panel is made of corrugated sheets with vertical tubes for the frame that run down either side. The tubes fit into standard or hi-visibility rubber block fence feet in order to support each panel.



30/40Kg

Durable

Secure



### Specifications

Size:	2.0m panel frame [H] x 2.1m [W] x 0.75mm [D] 2.4m panel frame [H] x 2.1m [W] x 0.75mm [D]
Weight:	30Kg / 40Kg
Material:	Pre-galvanised Steel / painted one side / powder coated one side
Colour:	Galvanised. Can be painted and powder coated specific to your RAL colour requirements (subject to a minimum order quantity and an additional cost)

### Key Features

- ✓ Easy to install and slot into standard or hi-visibility rubber block fence feet\*
- ✓ Increased strength from their corrugated galvanised steel sheets
- ✓ Deterrent against graffiti and vandalism
- ✓ Can be used with infills\*
- ✓ Channel along top and bottom is bird mouthed to snugly fit flush around the tube and hold the steel sheets into place

### Budget Options

Perhaps you don't have the budget to purchase outright, we always have a variety of solutions for you.

- Hire for short or long term
- Used/second hand
- Buyback
- Lease or Finance

### Top Tip

This product can be customised with a company colours to match (minimum order quantity required).

Standard and anti-tamper fence couplers can be supplied at an additional cost.

Our Hoarding Panels can be used in conjunction with our [Mesh Pedestrian Gate](#) and [Mesh Vehicle Gate](#).

### Contact Us

[elite-gss.com](http://elite-gss.com)

[sales@elite-gss.com](mailto:sales@elite-gss.com)



## Construction Sites



## Festivals and Outdoor Events



## Demolition



## Civil Engineering /Infrastructure



### How are they installed?

Hoarding Panels are connected to one another using standard or anti-tamper fence couplers\*. It's recommended to use two couplers per connection, one on the top of the panel and another at the bottom to ensure the system is well connected.



### Installation timings

Straightforward installation and quick assembling to secure unsafe areas with staff and equipment.



**2 people required to lift. Spanner required for the couplers\***




**Single connection in less than 5 mins**



**100 linear metres in approx. 2.5 hours (depending on ground conditions and site layout)**

### Accessorise and strengthen this solution

Pedestrians can access through the Portable hoarding system by inserting a Standalone Pedestrian Gate\*. For Vehicles, we also have the Mesh Vehicle Gate\*.



Co-ordinated infills and ground skirts and ensure that there are no gaps in your temporary hoarding system.

To make the system more secure in adverse weather conditions, the steel hoarding system must be re-enforced using stabilisers and block tray systems.

## Additional information



**Technical and Installation Guide**



**Elite Products Brochure**

## Need to Natter?

☎ 0800 622 6838

🌐 elite-gss.com

📘 News, insights and events

🐦 Product reviews and offers, answered questions and discussion tips

📺 Shared business and industry information

📺 'How to' use our products, installations and vlogs



**Wind loading calculation must be carried out prior to use.**

**\* Products are sold separately - ask us with your enquiry.**