

556 Cushion Ease Solid™

Heavy duty modular rubber tiles



Ergonomic, Anti-fatigue & Safety Matting - Dry Areas Modular Matting 556 Cushion Ease Solid™

Ergonomic benefit derived from a 19 mm thick worker platform with a closed anti-slip pebble structure surface for maximum anti-fatigue comfort in dry industrial environments.

- Heavy duty rubber tiles can be easily assembled for coverage of large areas or individual workstations, wall-to-wall or as islands
- 100% natural rubber compound
- Compatible with patented MD Ramp System™ for smart safety beveling solutions; allows outside and inside corners

Recommended use

- Dry Areas
- For placement in manufacturing plants, assembly lines, picking, packing and logistics warehouses, individual work stations.
- Heavy duty

Colors:


- Black

Sizes:

- 91cm x 91cm
- per m2

Accessories:

- 552 MD-X Ramp System™ Nitrile
- INS Installation Service Available on Request
- 651 M.D. Fire Retardent Ramp System
- 551 MD Ramp System™ Nitrile



WEAR RESISTANCE

SLIP RESISTANCE

ANTI-FATIGUE

GOOD BETTER BEST



Ergonomic, Anti-fatigue & Safety Matting - Dry Areas Modular Matting Cushion Ease Solid™

General

Brand	Notrax
Category	Dry Areas Modular Matting
Product Number	556
Product Family	Industrial & Commercial Matting
Product Group	Ergonomic, Anti-fatigue & Safety Matting
Product Name	Cushion Ease Solid™
Recommended use	For placement in manufacturing plants, assembly lines, picking, packing and logistics warehouses, individual work stations.
Series	Cushion-Ease®
Shipping Location	Achterzeedijk 57, Unit 15, Barendrecht 2992SB, The Netherlands, Chicago, IL 60638, United States
Type	Dry Areas - Heavy Duty Modular Rubber Mats
Update trigger	20210310-1301
Usage Intensity	Heavy duty

Sustainability

REACH	Reach compliant (Registration, Evaluation, Authorization and Restriction of Chemicals).
Recycled	True
Rohs US	Rohs compliant (Restriction of Hazardous Substances).
Sustainability	Recyclable material, Made from recycled material
Warranty (years)	1

Tests

Abrasion Resistance 1000	2.90g (5000 cycles)
Compression Deflection 1.4	33.3 lb/in ² (at 25%)
Compression Deflection 2.8	33.3 lb/in ² (at 50%)
Fire rating US	Pass
Hardness	67 Shore A
Slip Rating	R9
Coefficient Friction Dry	0.68
Surface Flammability	Pass
Tear Strength	55.4 lb

Technical Specifications

Application	Industrial Environments
Breaking Load	44 lb
Edges	Attachable bevelled edges are available
Material	Natural rubber
Material Group	Natural rubber
Process	Compression Moulding
Temperature Range	- 40 ° C up to + 120 ° C

Cushion Ease Solid™ Black

Art. nr.	Dimension (cm)	Weight (kg)	Thickness (mm)	Recommended accessories
556S0000BL	per m2	13.6	19	INSTALL004
556S0033BL	91cm x 91cm	12.7	19	

Accessories

552 MD-X Ramp System™ Nitrile INS Installation Service Available on Request 651 M.D. Fire Retardent Ramp System 551 MD Ramp System™ Nitrile